

Powerman Vario without punch kit



Features

- Can also be used for hard to reach housing areas

Product Description

- Allround swing and pivot cylinder

Technical Data

- Suitable for:
 - Round punches to Ø 3.15"
 - Square punches to 2.68"
 - Rectangular punches to 3.78" diagonal
- Capable of cutting:
 - Sheet steel up to max. 10 ga
 - Stainless steel up to max. 14 ga
 - Aluminum up to max. 7 ga

- dependent on punch size
- cutting pressure: 50 kN
- Oil filling: 0.17 l
- screw holder: 19 mm; 0.75 inch

Scope of Delivery

- Hydraulic pump
- 2 Bolts
- 1 Reduction piece
- 1 Case


Accessories

- spacer → below
- bolts → below
- bushing → below


| Description | Weight | | Order No. |
|----------------------------------|--------|------|-----------------|
| | kg | lbs | |
| Powerman Vario without punch kit | 3.5 | 7.72 | 2626-7200-01-00 |

Accessories


Spacer Details → page 81

|  | D1 | | D2 | | length | | Order No. |
|---|------|------|----|------|--------|------|-----------------|
| | mm | inch | mm | inch | mm | inch | |
| | 10 | 0.39 | 35 | 1.38 | 8 | 0.31 | 2624-0710-08-00 |
| | 19.5 | 0.77 | 35 | 1.38 | 10 | 0.39 | 2624-0510-19-00 |
| | 19.5 | 0.77 | 36 | 1.42 | 18 | 0.71 | 2622-0719-03-00 |

Bolts Details → page 80

|  | D1 | | D2 | | length | | Order No. |
|---|------|------|-----|------|--------|------|-----------------|
| | mm | inch | mm | inch | mm | inch | |
| | 19 | 0.75 | 19 | 0.75 | 120 | 4.72 | 2624-0719-00-00 |
| | 11.1 | 0.44 | 19 | 0.75 | 100 | 3.94 | 2624-0711-19-00 |
| | 9.5 | 0.37 | 9.5 | 0.37 | 87 | 3.43 | 2624-0710-00-00 |

Bushing

|  | D1 | | D2 | | length | | Order No. |
|---|-----|------|----|------|--------|------|-----------------|
| | mm | inch | mm | inch | mm | inch | |
| | 9.5 | 0.37 | 19 | 0.75 | 40 | 1.57 | 2624-0719-10-01 |