

## Powerman Accu without punch kit



### Features

- Quick and easy punching

### Product Description

- Battery-powered hydraulic punch; microprocessor controlled and 12 Volt battery-powered
- Only 8 seconds punching time for a 2.5" dia. hole in 12 ga mild steel sheet
- 9 lbs weight of hydraulic punch, without tools

### Technical Data

- Suitable for:
- Round punches to Ø 4.02"
- Square punches to 3.62"
- Rectangular punches to 4.53" diagonal
- Capable of cutting:
- Mild steel 12 ga

- Stainless steel 14 ga
- Aluminum 11 ga
- dependent on punch size
- cutting pressure: 60 kN
- Oil filling: 0.1 l
- cylinder stroke: 22 mm; 0.87 inch
- battery: 12 V, 2 Ah
- screw holder: 19 mm; 0.75 inch

### Scope of Delivery

- Battery-powered hydraulic punch
- 2 Bolts
- 1 Reduction piece
- 1 Spacer
- 1 Battery charger
- 1 Battery cartridge
- 1 Case

Description	Weight		Order No.
	kg	lbs	
Powerman Accu without punch kit	8.5	18.74	2629-7100-01-00

## Powerman Accu with punch kit



### Features

- Quick and easy punching

### Product Description

- M1: With metric punch kit: M12, M16, M20, M25, M32, M40, M50, M63
- Plus: With metric round punch kit Plus M12, M16, M20, M25, M32, M40, M50 for stainless steel. With additional bolt Ø 11,1 mm.
- Battery-powered hydraulic punch; microprocessor controlled and 12 Volt battery-powered
- Only 8 seconds punching time. hole in 12 ga mild steel sheet
- 9 lbs weight of hydraulic punch, without tools

### Technical Data

- Suitable for:
- Round punches to Ø 4.02"
- Square punches to 3.62"
- Rectangular punches to 4.53" diagonal
- Capable of cutting:
- Mild steel 12 ga
- Stainless steel 14 ga

- Aluminum 11 ga
- dependent on punch size
- cutting pressure: 60 kN
- Oil filling: 0.1 l
- cylinder stroke: 22 mm; 0.87 inch
- battery: 12 V, 2 Ah
- screw holder: 19 mm; 0.75 inch

### Scope of Delivery

- Battery-powered hydraulic punch
- 2 Bolts
- 1 Reduction piece
- 1 Spacer
- 1 Punch kit
- 1 Battery charger
- 1 Battery cartridge
- 1 Case

### Accessories


- spacer → page 12
- bolts → page 12
- bushing → page 12
- alternate battery → page 12
- alternate charger → page 12

Description	Weight		Order No.
	kg	lbs	
Powerman Accu M1	11	24.26	2629-7100-02-00
Powerman Accu Plus	10	22.05	2629-7100-03-00


# Stamping pumps

## Accessories


### Spacer [Details → page 81](#)

	D1		D2		length		Order No.
	mm	inch	mm	inch	mm	inch	
	19.5	0.77	35	1.38	10	0.39	<b>2624-0510-19-00</b>


### Bolts [Details → page 80](#)

	D1		D2		length		Order No.
	mm	inch	mm	inch	mm	inch	
	19	0.75	19	0.75	120	4.72	<b>2624-0719-00-00</b>
11.1	0.44	19	0.75	100	3.94	<b>2624-0711-19-00</b>	
9.5	0.37	9.5	0.37	87	3.43	<b>2624-0710-00-00</b>	


### Bushing

	D1		D2		length		Order No.
	mm	inch	mm	inch	mm	inch	
	9.5	0.37	19	0.75	40	1.57	<b>2624-0719-10-01</b>

### Alternate battery

	Description	Order No.
	NI-MH 2,0 Ah, 12V	<b>2629-0000-05-00</b>

### Alternate charger

	Description	Order No.
	230V	<b>2629-0000-06-00</b>