

GNExB2LD2 LED Multifunction Beacon

The GNExB2LD2 is an IECEx & ATEX approved explosion proof high output LED multifunction beacon. The robust IP66 corrosion proof GRP enclosure and extended temperature range ensures the GNExB2LD2 is suitable for all Zone 1, 2, 21 & 22 hazardous location signalling applications.

The GNExB2LD2 beacons utilise an array of high output LED's oriented to optimise visibility in any direction. The beacon can be configured as a steady status indicator or one of the effective flashing modes may be used for warning applications. The field replaceable colour filter enhances the light output and is constructed from UV stable PC.

The GRP enclosure features a threaded flame path, triple cable entries and a large termination area - all of which significantly reduce installation time.

Features

- Robust, corrosion proof GRP (glass reinforced polyester) enclosure
- Ingress protection IP66
- Automatic synchronisation on multi-beacon systems
- Choice of five flash rates: 1Hz, 1.5Hz, 2Hz, double and triple flash.
- High and low power Steady modes
- Three remotely selectable stages/channels on DC versions.
- Glass lens & Stainless Steel guard
- UV stable PC field replaceable lens colour filter
- Stainless steel fixings
- Triple cable entries
- Duplicate cable terminations (in & out for daisy-chain installations)


Approvals

- IECEx UL 15.0003X
IEC 60079-0 : 2011
IEC 60079-1 : 2014
IEC 60079-31 : 2013
- ATEX DEMKO 15ATEX1448X
EN 60079-0 : 2012
EN 60079-1 : 2014
EN 60079-31 : 2014

Coding

- II 2G Ex db IIC Gb T6 Ta -50°C to +65°C
- II 2G Ex db IIC Gb T5 Ta -50°C to +70°C
- II 2D Ex tb IIIC Db T85°C Ta -50°C to +70°C





Specification

Source:	Array of 4 x High Power Cree® LED's
Modes:	1Hz flash (60 fpm) 1.5Hz flash (90 fpm) 2Hz flash (120 fpm) Double strike flash Triple strike flash High Power Steady Low Power Steady
Eff. Intensity cd:	174 cd - High Power Steady
Eff. Intensity cd:	338 cd - 1Hz flash
Lens colours:	Amber, Blue, Clear, Green, Magenta, Red & Yellow
Voltages DC:	24vdc
Voltages AC:	115Vac; 230Vac
Ingress protection:	IP66
Enclosure matl:	UV stable GRP (glass reinforced polyester)
Colour:	Natural Red - can be provided in alternative colours
Cable entries:	3 x M20 ISO (2 stopping plugs inc.) Adaptors to M25, 1/2" & 3/4" NPT can be specified
Terminals:	0.5 to 2.5mm ²
Enclosure volume:	<2 litres
Line monitoring:	Blocking diode included EOL Min. 500 Ohm 2w, or 3k3 Ohm 0.5w resistor or diode (DC versions) can be fitted
LED life:	60,000 Hours
Temperature range:	-50° to +70°C (-58°F to +158°F)
Weight:	3.5kg/7.7lbs
*All candela data is representative of performance with clear lens at optimum voltage.	

Example part code: GNExB2LD2AC230 [e][m][s][V][x][y]
GNExB2LD2AC230AB1A1R/R
GNExB2LD2 LED Beacon, 230V ac,
3 x M20 entries, Brass stopping plugs,
A2 304 SS guard, IECEx & ATEX approved,
Red enclosure, Red lens

Part Codes

Version:	Part code:
Product type:	GNExB2
Type:	LD2 LED Multifunction Beacon
Voltage:	DC024 18-54V dc AC115 103.5-126.5V ac AC230 207-253V ac
Cable Entry Type: [e]	A 3 x M20x1.5mm B 2 x 1/2" NPT - adaptors C 2 x 3/4" NPT - adaptors D 2 x M25x1.5mm - adaptors E 1 x 1/2" NPT - adaptor F 1 x 3/4" NPT - adaptor G 1 x M25x1.5mm - adaptor H 3 x 1/2" NPT - adaptors I 3 x 3/4" NPT - adaptors J 3 x M25x1.5mm - adaptors
Adaptor/Stopping plug material: [m]	B Brass (standard) N Nickel Plated S Stainless Steel
Guard material: [s]	1 A2 304 Stainless (standard) 2 A4 316 Stainless Steel
Product version: [v]	A1 IECEx & ATEX Group II 2G/D Zone 1, 2, 21 & 22
Enclosure colour: [x]	R Red S Special (contact E2S)
Lens colour: [y]	A Amber B Blue C Clear G Green M Magenta R Red Y Yellow

Current Consumption

Version:	Voltage:	Steady High Power Current:	Steady Low Power Current:	Flashing 1Hz Current:
24V dc	18-54V dc	240mA	134mA	110mA
115V ac	103.5-126.5V ac 50/60Hz	95mA	78mA	90mA
230V ac	207-253V ac 50/60Hz	48mA	37mA	45mA