

B100LDA Panel Mount L.E.D. permanent beacon

The B100 series is comprised of a Xenon strobe beacon, permanent filament bulb, blinking filament bulb and a permanent LED array beacon version.

The panel mount base incorporates a pluggable terminal block ensuring rapid installation and maintenance.

Part codes: Version: Part code: 10-30V dc B100LDA030B/[x] 90-230V ac B100LDA230B/[x] [x] = Lens colour: A: Amber B: Blue C: Clear G: Green R: Red

Y: Yellow


Features:

- Bayonet fixing lens.
- Anti-tamper locking screw.
- Stainless steel fixings.











Specification:

Light source:	9 x High power L.E.D's
Lens/L.E.D. colours:	Amber, Blue, Clear (White L.E.D), Green, Red & Yellow
Lens type:	Prismatic (standard) or plain
Mounting:	Panel mount PG29
Peak/Effective Intensity cd:	5.5cd*
Ingress protection:	IP65
Housing material:	High impact UL94 V0 (f1) PC
Terminals:	0.5 to 1.5mm ² pluggable
Operating temperature:	-25 to +50°C
Storage temperature:	-40 to +70°C
Relative humidity:	90% at 20°C.
Weight:	93g

 $^{^{\}star}\text{Candela}$ measurements representative of performance with amber lens at optimum voltage.

Current consumption:

Version:	Current mA:
10-30V dc	80mA
90-230V ac	50/60Hz 32mA

