

E2S22D \varnothing 22mm Buzzers & Pilot Lights

The E2S-22D range includes buzzers, combination units and pilot lights featuring super bright multichip L.E.Ds. Ingress protection to IP65, low current consumption and unsurpassed reliability under extreme conditions are all standard features of the E2S-22D range.

The range utilises screw terminals with wire guards for ease of installation and the ability to daisy chain the lights into an array.



Pilot Light:

Red

E2S22D12VR	12V ac/dc <80mA	12-chips Super-Bright
E2S22D24VR	24V ac/dc <80mA	12-chips Super-Bright
E2S22D48VR	48V ac/dc <20mA	12-chips Super-Bright
E2S22D130VR	110-130V ac/dc 25mA Max	12-chips Super-Bright
E2S22D230VR	230V ac 25mA Max	12-chips Super-Bright



Pilot Light:

Amber

E2S22D12VA	12V ac/dc <80mA	12-chips Super-Bright
E2S22D24VA	24V ac/dc <80mA	12-chips Super-Bright
E2S22D48VA	48V ac/dc <20mA	12-chips Super-Bright
E2S22D130VA	110-130V ac/dc 25mA Max	12-chips Super-Bright
E2S22D230VA	230V ac 25mA Max	12-chips Super-Bright



Pilot Light:

Green

E2S22D12VG	12V ac/dc <20mA	1-chip InGAN Ultra Super-Bright
E2S22D24VG	24V ac/dc <20mA	1-chip InGAN Ultra Super-Bright
E2S22D48VG	48V ac/dc <20mA	1-chip InGAN Ultra Super-Bright
E2S22D130VG	110-130V ac/dc 25mA Max	1-chip InGAN Ultra Super-Bright
E2S22D230VG	230V ac 25mA Max	1-chip InGAN Ultra Super-Bright



Pilot Light:

Blue


E2S22D12VB	12V ac/dc <20mA	2-chip InGAN Ultra Super-Bright
E2S22D24VB	24V ac/dc <20mA	2-chip InGAN Ultra Super-Bright
E2S22D48VB	48V ac/dc <20mA	2-chip InGAN Ultra Super-Bright
E2S22D130VB	110-130V ac/dc 25mA Max	2-chip InGAN Ultra Super-Bright
E2S22D230VB	230V ac 25mA Max	2-chip InGAN Ultra Super-Bright



Pilot Light:

White

E2S22D12VW	12V ac/dc <20mA	1-chip InGAN Ultra Super-Bright
E2S22D24VW	24V ac/dc <20mA	1-chip InGAN Ultra Super-Bright
E2S22D48VW	48V ac/dc <20mA	1-chip InGAN Ultra Super-Bright
E2S22D130VW	110-130V ac/dc 25mA Max	1-chip InGAN Ultra Super-Bright
E2S22D230VW	230V ac 25mA Max	1-chip InGAN Ultra Super-Bright



Buzzer:

E2S22DBZ
80 db at 10cm;
Current : 15-30mA;

Flashing pilot light:

E2S22DFS
Flash Rate: 2Hz;
Current : 15-30mA;

Combination:

E2S22DBF
80 db at 10 cm;
Current : 18-80mA;

Pilot lights:

E2S22D
Low voltage DC/AC:
Current : 20-80mA;
High voltage DC/AC:
Current : 18-25mA;

Buzzer:

80dB @ 10cm Current: 15-30mA

E2S22DBZ24V	24V dc/ac Buzzer
E2S22DBZ48V	48V dc/ac Buzzer
E2S22DBZ130V	110-130V ac/dc Buzzer
E2S22DBZ230V	230V ac Buzzer

Flashing Pilot Light:

Flash rate: 2Hz Current: 15-30mA

E2S22DFS24V	24V ac/dc 2x LED Red
E2S22DFS48V	48V ac/dc 2x LED Red
E2S22DFS130V	110-130V ac/dc 2x LED Red
E2S22DFS230V	230V ac 2x LED Red

Combination:

80dB @ 10cm With Red LED

E2S22DBF24V	24V ac/dc Buzzer & 2x LED Red lo: 20-80mA
E2S22DBF48V	48V ac/dc Buzzer & 2x LED Red lo: 20-80mA
E2S22DBF130V	110-130V ac/dc Buzzer & 2x LED Red lo: 18-30mA
E2S22DBF230V	230V ac Buzzer & 2x LED Red lo: 18-30mA

E2S22DMT

Mounting Tool for E2S-22D LED Pilot Lights

E2S22DLBHF25X18	E2S-22D Label holder 25x18mm
E2S22DLBHF25X10	E2S-22D Label holder 25x10mm

