

# IECEx Certificate of Conformity

# INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification Scheme for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.:

IECEx BVS 07.0014

issue No.:1

Certificate history:

Issue No. 1 (2009-8-13) Issue No. 0 (2007-8-2)

Status:

Current

Date of Issue:

2009-08-13

Page 1 of 4

Applicant:

Steute Schaltgeräte GmbH & Co.

Brückenstraße 91 32584Löhne **Germany** 

Electrical Apparatus: Optional accessory:

Posit

Position switch type EEx 335

Type of Protection:

Flameproof enclosure "d"; increased safety "e"; Protection by enclosures "tD"

Marking:

Ex de IIC T6/T5

Ex tD A21 IP67 T80°C/T95°C

Approved for issue on behalf of the IECEx

Certification Body:

Dr. F. Eickhoff

Position:

Deputy Head of Certification Body

Signature:

(for printed version)

Date:

2009-01-13

1. This certificate and schedule may only be reproduced in full.

2. This certificate is not transferable and remains the property of the issuing body.

3. The Status and authenticity of this certificate may be verified by visiting the Official IECEx Website.

Certificate issued by:

DEKRA EXAM GmbH Dinnendahlstrasse 9 44809 Bochum Germany





# **IECEx Certificate** of Conformity

Certificate No.:

IECEx BVS 07.0014

Date of Issue:

2009-08-13

Issue No.: 1

Page 2 of 4

Manufacturer:

Steute Schaltgeräte GmbH & Co.

Brückenstraße 91 32584 Löhne Germany

## Manufacturing location(s):

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

#### STANDARDS:

The electrical apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 60079-0: 2004

Electrical apparatus for explosive gas atmospheres - Part 0: General requirements

Edition: 4.0

IEC 60079-1: 2003

Electrical apparatus for explosive gas atmospheres - Part 1: Flameproof enclosure 'd'

Edition: 5

IEC 60079-7: 2006-07

Explosive atmospheres - Part 7: Equipment protection by increased safety "e"

Edition: 4

IEC 61241-0: 2004

Electrical apparatus for use in the presence of combustible dust - Part 0: General

Edition: 1

requirements

IEC 61241-1: 2004

Electrical apparatus for use in the presence of combustible dust - Part 1: Protection by

enclosures "tD" Edition: 1

This Certificate does not indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.

### **TEST & ASSESSMENT REPORTS:**

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

#### Test Report:

DE/BVS/ExTR07.0017/01

Quality Assessment Report: DE/BVS/QAR06.0023/02



# IECEx Certificate of Conformity

Certificate No.:

IECEx BVS 07.0014

Date of Issue:

2009-08-13

Issue No.: 1

Page 3 of 4

#### Schedule

# **EQUIPMENT:**

Equipment and systems covered by this certificate are as follows:

### General product information:

The dots in the type designation EEx 335 of the position switch will be replaced regarding actuation and contact function by the other characters.

The position switch type EEx 335 is designed in type of protection increased safety "e" and in type of protection bey enclosure "tD". The position switch type EEx 335 is equipped with a switch insert in type of protection flameproof enclosure "d".

The position switch is suitable for the application in areas potentially hazardous by combustible gases and dusts.

## Ratings:

Rated switching voltage	DC AC	230 250	V V
Rated switching current	DC	0.25	A
Utilization category	AC DC	6 13	А
	AC	15	
Rated connecting Capacity		1.5	mm <sup>2</sup>

Ambient temperature range

-20 °C ≤Tamb ≤+40 °C for T6 and T 80 °C -20 °C ≤Tamb ≤+60 °C for T5 and T 95 °C

### CONDITIONS OF CERTIFICATION: NO



# IECEx Certificate of Conformity

Certificate No.:

IECEx BVS 07.0014

Date of Issue:

2009-08-13

Issue No.: 1

Page 4 of 4

		OLIANIOEO (C.		
DETAILS O	F CERTIFICATE	CHANGES (10)	issues i	anu abovei.

The position switch now fulfils the requirements for ingress protection IP67.