

IECEx Certificate of Conformity

	ertification Sche	CTROTECHNICAL me for Explosive	Atmospheres
Certificate No.:	IECEx SIR 13.0029X	issue No.:0	Certificate history:
Status:	Draft		
Date of Issue:	2013-02-13	Page 1 of 4	
Applicant:	European Safety Syste Inpress House Mansell Road London W3 7QH United Kingdom	ems Ltd.	
Electrical Apparatus: Optional accessory:	GNEx Series Sounder/Lo	oudspeaker	
Type of Protection:	Flameproof		
Marking:	Ex d II* T* Gb * Refer to the description		
Approved for issue on b Certification Body:	ehalf of the IECEx	C Ellaby	
Position:		Deputy Certification Manager	
Signature: (for printed version)			
Date:			
This certificate is not t		ced in full. property of the issuing body. be verified by visiting the Officia	I IECEx Website.
Certificate issued by: SIR	A Certification Service Rake Lane Eccleston Chester CH4 9JN United Kingdom	-	Sira

ECIECEx Certificateof Conformity				
Certificate No.:	IECEx SIR 13.0029X			
Date of Issue:	2013-02-13	Issue No.: 0		
		Page 2 of 4		
Manufacturer:	European Safety Syst Inpress House Mansell Road London W3 7QH United Kingdom	ems Ltd.		
Additional Manufacturing lc (s):	cation			
found to comply with the IE covered by this certificate, v	C Standard list below and that the was assessed and found to comply	esentative of production, was assessed and tested anc manufacturer's quality system, relating to the Ex products y with the IECEx Quality system requirements. This CEx Scheme Rules, IECEx 02 and Operational Documents		
STANDARDS: The electrical apparatus an documents, was found to c	d any acceptable variations to it s omply with the following standards	pecified in the schedule of this certificate and the identified		
IEC 60079-0 : 2011 Edition: 6.0	Explosive atmospheres - Part 0:	General requirements		
IEC 60079-1 : 2007-04 Edition: 6	Explosive atmospheres - Part 1	Equipment protection by flameproof enclosures "d"		
This Certificate does not	t indicate compliance with electrica expressly included in the	al safety and performance requirements other than those Standards listed above		
TEST & ASSESSMENT RI A sample(s) of the equipme		examination and test requirements as recorded in		
<u>Test Report:</u> GB/SIR/ExTR13.0217/00				
Quality Assessment Report	<u>:</u>			
GB/SIR/QAR06.0020/03				

	IECEx Certificate of Conformity						
Certificate No .:	IECEx SIR 13.0029X						
Date of Issue:	2013-02-13	Issue No.: 0					
		Page 3 of 4					
Schedule							
EQUIPMENT: Equipment and systems co	overed by this certificate are as follows.						
The GNEx Series Sounde generates sound, control metal wire element which	er/Loudspeaker consists of a GRP, flar circuitry and terminals for connection t is cemented into the enclosure for the I lid for access and cable entry is via u	meproof enclosure which contains a pressure unit that to external circuits. The enclosure has a pressed e transmission of sound from the enclosure. The p to two, M20 x 1.5 threaded entries. Both internal					
seconds as req	omply with the following: shall be subjected to a routine overpr	essure test of at least 23.05 bar for at least 10 1. There shall be no permanent deformation or ge through the enclosure wall					
CONDITIONS OF CERTIFI	ICATION: YES as shown below:						
level of electros it may be subje	static charges. The user shall ensure t cted to external conditions (such as hig arges on non-conducting surfaces. Ac	xtreme conditions, may generate an ignition-capable hat the equipment is not installed in a location where gh-pressure steam) which might cause a build-up of Iditionally, cleaning of the equipment should be done					



IECEx Certificate of Conformity

Certificate No .:

IECEx SIR 13.0029X

Date of Issue:

2013-02-13

Issue No.: 0

Page 4 of 4

EQUIPMENT(continued):

The equipment has the following gas groups, temperature classes and ambient temperature ranges:						
Type (Description)	Option (Rating)	Gas group	Temp. class	Ambient temp.		
GNExS1****	GNExS1DC024 (10 – 30 V dc)	IIC	T4	-60°C to +50°C		
(110 dB Small Sounder)	GNExS1DC048 (48 V dc)	IIC	T3	-60°C to +70°C		
	GNExS1AC230 (100 – 260 V ac/dc)	IIB	T6	-60°C to +50°C		
		IIB	T5	-60°C to +65°C		
		IIB	T4	-60°C to +70°C		
GNExS2****	GNExS2DC024 (10 – 30 V dc)	IIC	T4	-60°C to +50°C		
(117 dB Small Sounder)	GNExS2DC048 (48 V dc)	IIC	Т3	-60°C to +58°C		
	GNExS2AC230 (100 – 260 V ac)	IIB	T6	-60°C to +50°C		
		IIB	T5	-60°C to +58°C		
GNExL1****	GNExL1V100 (100/70 V Line)	IIC	T4	-60°C to +50°C		
(15 W Loudspeaker)	GNExL1R016 (16 Ohm)	IIC	T3	-60°C to +70°C		
	GNExL1R008 (8 Ohm)	IIB	T6	-60°C to +50°C		
		IIB	T5	-60°C to +65°C		
		IIB	T4	-60°C to +70°C		
GNExL2****	GNExL2V100 (100/70 V Line)	liC	T4	-60°C to +50°C		
(25 W Loudspeaker)	GNExL2R016 (16 Ohm)	IIC	T3	-60°C to +65°C		
	GNExL2R008 (8 Ohm)	IIB	T6	-60°C to +50°C		
		IIB	T5	-60°C to +65°C		