

# SONF1 Alarm Sounder

The SONF1 is a compact, high output, 100dB(A) alarm sounder. Low current consumption and high SPL in a robust fire retardant housing ensure the SONF1 is suitable for all general signalling applications including fire, security and process control.

## Features:

- Automatic synchronisation on multi-sounder system.
- Continuously rated.
- Stainless steel fixings.
- Mounting via internal BESA compatible fixing positions (standard version) or via external mounting lugs.
- Duplicate cable terminations (in & out for daisy-chain installations).
- Tropicalisation available on request.
- Available with custom tone configurations and frequencies.

## Approvals:

- VdS approved to EN54-3 (CPD 89/106/EEC).
- UKOOA/PFEER compliant alarm tones.
- UL approved version available.
- GOST-R approved. Cert: POCC GB-JB05-B02228

## Part codes:

Version:	Part code:
24V dc	SONF1DC24[x]
24V ac	SONF1AC24[x]
115V ac	SONF1AC115[x]
230V ac	SONF1AC230[x]

Suffix part number with '-UL' for UL approved version

## A100 back box with mounting lugs:

24V dc	SONF1DC24A[x]
24V ac	SONF1AC24A[x]
115V ac	SONF1AC115A[x]
230V ac	SONF1AC230A[x]
[x] = Housing colour:	G: Grey R: Red W: White



0786-CPD-20191




G205054



Available as the SONFL1 alarm horn sounder & beacon combination unit.





**Specification:**

Maximum output:	100dB(A) @ 1 metre
Nominal output:	99dB(A) @ 1m +/- 3dB - Tone 1
No. of tones:	10 (UKOOA / PFEER compliant)
No. of stages:	2
Volume control:	On board potentiometer
Effective range:	30m @ 1KHz
Voltages DC:	24V dc (10-30V dc) Reverse polarity diode protection on DC units.
Voltages AC:	24V ac; 115V ac; 230V ac
Ingress protection:	IP55 (UL version Type 13 & 3R ) (IP56 with optional WR kit)
Housing material:	High impact UL94 V0 & 5VA FR ABS
Colour:	Red (RAL3000), grey (RAL7038) & white.
Cable entries:	4 x M20 clearance gland knockouts in side & back
Terminals:	0.5 to 1.5mm <sup>2</sup> cables.
Operating temperature:	-25 to +55°C
Storage temperature:	-40 to +70°C
Relative humidity:	90% at 20°C.
Weight :	0.30kg

\*SPL data +/-3dB(A). Measured at optimum voltage.

**Alarm sander:**

Version:	Voltage range:	Current mA:
24V dc	10-30V dc	25mA
24V ac	50/60Hz +/-10%	40mA
115V ac	50/60Hz +/-10%	13mA
230V ac	50/60Hz +/-10%	13mA

**SONF1 24V dc tone table:**

Stage 1	Frequency Description	dB @ 1m	Stage 2
Tone 1	800/1000Hz @ 0.25 sec Alternating - BS5839 Alarm tone	99dB(A) @ 1m	Tone 8
Tone 2	500/1200Hz @ 0.3Hz 0.5 sec Slow Whoop - NEN 2575:2000	100dB(A) @ 1m	Tone 1
Tone 3	1200/500Hz @ 1Hz - DIN / PFEER P.T.A.P.	99dB(A) @ 1m	Tone 8
Tone 4	544Hz (100mS)/440Hz (400mS) - AFNOR NF S 32-001	97dB(A) @ 1m	Tone 9
Tone 5	Bell	95dB(A) @ 1m	Tone 1
Tone 6	800/1000Hz @ 7Hz Sweeping	99dB(A) @ 1m	Tone 8
Tone 7	500-1200Hz 3.75sec /0.25sec. Australian Evac.	100dB(A) @ 1m	Tone 10
Tone 8	1000Hz Continuous - PFEER toxic gas	100dB(A) @ 1m	-
Tone 9	554Hz Continuous	97dB(A) @ 1m	-
Tone 10	420Hz @ 0.625 sec Australian Alert	97dB(A) @ 1m	-

**SONF1 115V ac and 230V ac tone table:**

Stage 1	Frequency Description	dB @ 1m
Tone 1	800/1000Hz @ 0.25 sec Alternating - BS5839 Alarm tone	99dB(A) @ 1m
Tone 2	500/1200Hz @ 0.3Hz 0.5 sec Slow Whoop - NEN 2575:2000	100dB(A) @ 1m
Tone 3	1200/500Hz @ 1Hz - DIN / PFEER P.T.A.P.	99dB(A) @ 1m
Tone 4	544Hz (100mS)/440Hz (400mS) - AFNOR NF S 32-001	97dB(A) @ 1m
Tone 5	1000Hz Continuous - PFEER toxic gas	100dB(A) @ 1m
Tone 6	Bell	95dB(A) @ 1m
Tone 7	800/1000Hz @ 7Hz Sweeping	99dB(A) @ 1m
Tone 8	2400/2900Hz @ 50Hz Sweeping	100dB(A) @ 1m
Tone 9	420Hz @ 0.625 sec Australian Alert	97dB(A) @ 1m
Tone 10	500-1200Hz 3.75sec /0.25sec. Australian Evac.	100dB(A) @ 1m

Country specific or custom tone configurations and alarm frequencies are available upon request.