

ADALIT L-5000

Features

● Rechargeable HAND LAMP

Ingress protection: IP66.

Weight: 1,1 Kg.

Measures: 26 x 11 x 11 cm.

LED Engine optic: 7 LEDs (1 x 3W high power-spot beam and strobe function / 2 x flood light / 2 x signalling-blue or amber light / 2 x tail beacon-red light).

Burning time: 3 different light setting 3/6/12 hours.

Torch body material: Thermoplastic resin with high resistance to the impacts, extreme temperatures and corrosive substances.

Swivelling head: -30° / 0° / 30° / 60° / 90°.

Lighting source: 160.000 candle power.

Switches: Two button switches of soft touch material ergonomic and oversized to guarantee easy pushing.

Main: On/Off and light setting. Tail light On. Strobe function.

Auxiliary: Flood light mode. Signalling-blue or amber light.

Battery: Rechargeable Li-ion | Voltage: 3,7 V. | 8800 mAh.

Accessories: Shoulder strap - included.



● CHARGER

Marking: CE e9.

Ingress protection: IP54.

Charging time: 8 h.

Disconnection at the end of the charge: Automatic.

Charge indication: Red LED: charging | Green LED: charged.

Feeding source: DC 12 V. / 24 V. | AC: 100/240 V. 50/60 Hz.



SWIVELLING HEAD

-30° 0° 30° 60° 90°



www.adalit.com

●●● The Light Company
ADARO

ADARO Tecnología, S.A.
Parque Científico y Tecnológico de Gijón
-EDIFICIO ADARO-
33203 GIJÓN-ASTURIAS-SPAIN

Customer Service
Tel.: +34 985 347 806
Fax: +34 985 358 378
info@adalit.com