

IECEx Certificate of Conformity

Page 1 of 3

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification Scheme for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

R C Marshall

Certificate No.: IECEx CML 19.0101X Issue No: 0 Certificate history:

Issue No. 0 (2019-09-06)

Status: Current

Date of Issue: 2019-09-06

Applicant: Peppers Cable Glands Limited

Stanhope Road, Camberley, Surrey, GU15 3BT

United Kingdom

Equipment: RA** Range of Rotating Adaptors Reducers and Elbows

Optional accessory:

Type of Protection: Flameproof "db", Increased Safety "eb", Restricted Breathing "nR", Dust Ignition "ta"

Marking:

Ex db I Mb Ex db IIC Gb Ex eb I Mb Ex eb IIC Gb Ex nR IIC Gc Ex ta IIIC Da

Ts = -60°C to +135°C IP66 / IP68 (100 m for 7 days)

Approved for issue on behalf of the IECEx

Certification Body:

Position: Certification Officer

Signature:

(for printed version)

Date: 2019-09-06

- 1. This certificate and schedule may only be reproduced in full.
- 2. This certificate is not transferable and remains the property of the issuing body.
- 3. The Status and authenticity of this certificate may be verified by visiting the Official IECEx Website.

Certificate issued by:

Eurofins E&E CML Limited
Unit 1, Newport Business Park
New Port Road
Ellesmere Port, CH65 4LZ
United Kingdom







IECEx Certificate of Conformity

Certificate No: IECEx CML 19.0101X Issue No: 0

Date of Issue: 2019-09-06 Page 2 of 3

Manufacturer: Peppers Cable Glands Limited

Stanhope Road, Camberley, Surrey, GU15 3BT

United Kingdom

Additional Manufacturing location(s):

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

STANDARDS:

The apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 60079-0 : 2017 Explosive atmospheres - Part 0: Equipment - General requirements

Edition:7.0

IEC 60079-1: 2014-06 Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d"

Edition:7.0

IEC 60079-15 : 2017 Explosive atmospheres - Part 15: Equipment protection by type of protection "n"

Edition:5.0

IEC 60079-31 : 2013 Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure "t"

Edition:2

IEC 60079-7: 2017 Explosive atmospheres - Part 7: Equipment protection by increased safety "e"

Edition:5.1

This Certificate **does not** indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

Test Report:

GB/CML/ExTR19.0164/00

Quality Assessment Report:

GB/SIR/QAR06.0018/09



IECEx Certificate of Conformity

Certificate No:	IECEx CML 19.0101X	Issue No: 0
-----------------	--------------------	-------------

Date of Issue: **2019-09-06** Page 3 of 3

Schedule

EQUIPMENT:

Equipment and systems covered by this certificate are as follows:

The RA** range of rotating adaptors, reducers and elbows are constructed from brass or stainless-steel hexagonal shape extrusion or block of material machined to form a 90° elbow.

Refer to Annex for full description.

SPECIFIC CONDITIONS OF USE: YES as shown below:

Refer to Annex for specific conditions of use.

Annex:

IECEx CML 19.0101X Iss. 0 Certificate Annex.pdf

Annexe to: IECEx CML 19.0101X Issue 0

Applicant: Peppers Cable Glands Limited

Apparatus: RA** Range of Rotating Adaptors

Reducers and Elbows



Product description

The RA** range of rotating adaptors, reducers and elbows are constructed from brass or stainless-steel hexagonal shape extrusion or block of material machined to form a 90° elbow. The ends are machined to form optional male and female entry thread connections as indicated below:

KE.	v٠	METRIC									NPT, BSPP, BSPT & NPSM									PG										ET									
KEY: = ADAPTOR = REDUCER		M12	M16	M20	M25	M32	M40	M50	M63	M75	M80	M85	1/4"	3/8"	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"	PG7	PG9	PG11	PG13.5	PG16	PG21	PG29	PG36	PG42	PG48	1/2"	5/8"	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"
	M12	Α	Α	Α									Α	Α	Α							Α	Α	Α	Α					Н		Α	Α	Α					
	M16	R	Α	Α	Α								Α	Α	Α	Α						R	Α	Α	Α							Α	Α	Α	Α				
	M20	R	R	Α	Α	Α							R	Α	Α	Α	Α					R	R	Α	Α	Α	Α					R	R	Α	Α	Α			
2	M25	R	R	R	Α	Α	Α						R	R	R	Α	Α	Α				R	R	R	R	Α	Α	Α				R	R	R	Α	Α	Α		
METRIC	M32	R	R	R	R	Α	Α	Α					R	R	R	R	Α	Α	Α			R	R	R	R	R	Α	Α	Α			R	R	R	R	Α	Α	Α	
Σ	M40	R	R	R	R	R	Α	Α	Α				R	R	R	R	R	Α	Α	Α		R	R	R	R	R	R	Α	Α	Α		R	R	R	R	R	Α	Α	Α
	M50	R	R	R	R	R	R	Α	Α	Α			R	R	R	R	R	R	Α	Α	Α	R	R	R	R	R	R	R	R	Α	Α	R	R	R	R	R	R	Α	Α
	M63	R	R	R	R	R	R	R	Α	Α	Α	Α	R	R	R	R	R	R	R	Α	Α	R	R	R	R	R	R	R	R	R	Α	R	R	R	R	R	R	R	Α
	M75	R	R	R	R	R	R	R	R	Α	Α	Α	R	R	R	R	R	R	R	R	Α	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R
	M80	R	R	R	R	R	R	R	R	Α	Α	Α	R	R	R	R	R	R	R	R	Α	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R
N	M85	R	R	R	R	R	R	R	R	R	Α	Α	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R
	M90	R	R	R	R	R	R	R	R	R	R	Α	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R
	1/4"	Α	Α	Α			-		i i				Α	Α	Α		<u> </u>	-				Α	Α	Α	Α							Α	Α	Α					
	3/8"	R	Α	A	Α								Α	Α	A	Α						R	A	Α	Α							R	Α	Α	Α				
IPSI	1/2"	R	R	A	A	Α							R	A	A	A	Α					R	R	A	A	Α	Α					R	R	A	Α	Α			
Z	3/4"	R	R	R	A	A	Α						R	R	R	A	A	Α				R	R	R	R	Α	A	Α		Н		R	R	R	Α	A	Α		
NPT, BSPP, BSPT & NPSM	1"	R	R	R	R	A	A	Α					R	R	R	R	A	A	Α			R	R	R	R	R	A	A	Α			R	R	R	R	A	A	Α	-
	1-1/4"	R	R	R	R	R	A	A	Α				R	R	R	R	R	A	A	Α		R	R	R	R	R	R	A	A	Α		R	R	R	R	R	A	A	Α
	1-1/4"	R	R	R	R	R	R	A	A	Α			R	R	R	R	R	R	A	A	Α	R	R	R	R	R	R	R	Α	A	Α	R	R	R	R	R	R	A	A
, BS	2"	R	R	R	R	R	R	R	A	A	Α	Α	R	R	R	R	R	R	R	A	Α	R	R	R	R	R	R	R	R	R	A	R	R	R	R	R	R	R	A
ΙÞΤ	2-1/2"	R	R	R	R	R	R	R	R	A	Α	A	R	R	R	R	R	R	R	R	Α	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R
_	3"	R	R	R	R	R	R	R	R	R	Α	Α	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R
	PG7	Α	Α	Α		<u>.</u> ``	<u></u>		···		_	_	Α	Α	A			<u> </u>	<u> </u>			A	A	Α	Α		-:-				-	Α	A	Α	-		<u> </u>	-	
	PG9	Α	Α	A									Α	Α	A							A	A	Α	Α	Α						R	A	Α					
	PG11	R	A	A	Α								R	A	A	Α						R	A	Α	Α		Α					R	Α	A	Α				
	PG13.5	R	R	A	Α	Α							R	R	A	Α	Α					R	R	Α	Α	Α	Α					R	R	Α	Α	Α			
	PG16	R	R	A	A	A	Α						R	R	A	A	A					R	R	R	Α	Α	A					R	R	A	A	A			
ЬG	PG21	R	R	R	A	A	A						R	R	R	A	A	Α				R	R	R	R	R	A	Α				R	R	R	Α	A	Α		
	PG29	R	R	R	R	R	A	Α	Α				R	R	R	R	A	A	Α			R	R	R	R	R	R	A	Α			R	R	R	R	R	Α	Α	Α
	PG36	R	R	R	R	R	R	A	A	Α			R	R	R	R	R	A	A	Α		R	R	R	R	R	R	R	A	Α	Α	R	R	R	R	R	R	A	A
	PG30 PG42	R	R	R	R	R	R	A	A	A			R	R	R	R	R	R	R	A	Α	R	R	R	R	R	R	R	R	A	A	R	R	R	R	R	R	A	A
	PG42 PG48	R	R	R	R	R	R	R	A	A			R	R	R	R	R	R	R	A	A	R	R	R	R	R	R	R	R	R	A	R	R	R	R	R	R	R	A
	1/2"	Α	Α	A	Ë	<u></u>	Ë	L.	_	_			A	Α	Α	Ë	<u>"</u>	Ë	<u> </u>	_	_	A	Α	Α	Α			-`-	.,		_	Α	Α	Α		-:-	<u> </u>	-:-	<u> </u>
	5/8"	A	A	A	Α								A	A	A	Α						A	A	A	A	\dashv						A	A	A					
	3/4"	R	A	A	A	Α							R	A	A	A	Α					R	R	A	A	Α	Α			H		R	A	A	Α		-		
	3/4 1"	R	R	R	A	A	Α						R	R	R	A	A	Α				R	R	R	R	A	A	Α		H		R	R	R	A	Α	Α	-	
ы	1-1/4"	R	R	R	R	A	A	Α	-				R	R	R	R	A	A	Α			R	R	R	R	R	A	A	Α			R	R	R	R	A	A	Α	
ш	1-1/4	R	R	R	R	R	A		Α				R	R	R	R	R	A	A	_		R	R	R	R	R	R			Α	_	R	R	R	R	R	_	_	Α
	2"	R	R	R	R	R	R	A	A	Α			R	R	R	R	R	R	A	A	Α	R	R	R	R	R	R	A R	A	A	A	R	R	R	R	R	A R	A	A
	2-1/2"	R	R	R	R	R	R	R	A	A	Α	^	R	R	R	R	R	R	R	A	A	R	R	R	R	R	R	R	R	A	A	R	R	R	R	R	R	R	A
	3"	R	R	R	R	R	R	R	R	A	A	A	R	R	R	R	R	R	R	R	A	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R





Unit 1, Newport Business Park New Port Road Ellesmere Port CH65 4LZ

T +44 (0) 151 559 1160 **E** info@cmlex.com



The equipment comprises of two parts, linked together in which they can rotate whilst are interlocked. Once the parts are linked together, they form a cylindrical flameproof joint coupled with O-ring and snap ring to hold the two parts together. The internal or external threads at each end may be provided with the above thread options and configurations. The assembly is rated for IP66 and IP68 ratings.

The Types and Model numbers of the RA** Range of Rotating Adaptors Reducers and Elbows are as follows:

Туре	Adaptors/Reducers	Туре	Elbow
RAFF	Female to Female	RAFF 90	Female to Female Elbow
RAMF	Male to Female	RAMF 90	Male to Female Elbow
RAMM	Male to Male	RAMM 90	Male to Male Elbow

Conditions of Manufacture

None.

Specific Conditions of Use

The following conditions relate to safe installation and/or use of the equipment:

- i. The Adaptors, Reducers, and Elbows are manufactured with a cylindrical joint between the entry body and threaded ferrule. This joint shall not be repaired.
- ii. The Adaptors, Reducers, and Elbows shall not be used outside their service temperature range of -60°C to +135°C.