



IECEx Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification Scheme for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.: IECEx UL 15.0003X Issue No: 1 Certificate history:
Issue No. 1 (2016-06-30)
Status: **Current** Page 1 of 5 Issue No. 0 (2015-11-24)
Date of Issue: **2016-06-30**
Applicant: **European Safety Systems Limited**
Impress House
Mansell Road
Acton
London W3 7QH
United Kingdom
Equipment: **GNEEx range of Signalling Beacons and GNEExJ2 Junction Box**
Optional accessory:
Type of Protection: **Flameproof "db", Enclosure "tb"**
Marking:
Ex db IIC T6...T4 Gb
Ex tb IIIC T80°C...T130°C Db
-50°C to +40°C or
-50°C to +55°C or
-50°C to +65°C

-50°C to +70°C

Refer to Annex for Temperature Class

Approved for issue on behalf of the IECEx
Certification Body:

Aled Thomas

Position:

Project Engineer

Signature:
(for printed version)

Date:

1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting the [Official IECEx Website](http://www.iecex.com).



IECEx Certificate of Conformity

Certificate No: IECEx UL 15.0003X

Issue No: 1

Date of Issue: 2016-06-30

Page 2 of 5

Certificate issued by:

UL LLC
333 Pfingsten Road
Northbrook IL 60062-2096
United States of America





IECEX Certificate of Conformity

Certificate No: IECEx UL 15.0003X Issue No: 1

Date of Issue: 2016-06-30 Page 3 of 5

Manufacturer: **European Safety Systems Limited**
Impress House
Mansell Road
Acton
London W3 7QH
United Kingdom

Additional Manufacturing
location(s):

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

STANDARDS:

The electrical apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 60079-0 : 2011 Explosive atmospheres - Part 0: General requirements

Edition:6.0

IEC 60079-1 : 2014-06 Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d"

Edition:7.0

IEC 60079-31 : 2013 Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure "t"

Edition:2

*This Certificate **does not** indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.*

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

Test Report:

[US/UL/ExTR15.0005/01](#)

Quality Assessment Report:

[GB/SIR/QAR06.0020/05](#)



IECEx Certificate of Conformity

Certificate No: IECEx UL 15.0003X

Issue No: 1

Date of Issue: 2016-06-30

Page 4 of 5

Schedule

EQUIPMENT:

Equipment and systems covered by this certificate are as follows:

The GNExB1, GNExB2 series are a range of Electronic Strobe and LED Beacons housed in a Flameproof / Dust protected GRP enclosure that are intended to be used as visual warning / signaling devices. The enclosure is accessible via a threaded cover which incorporates a glass dome, the glass dome is cemented into the cover. The range is supplemented by a GNExJ2 Junction Box which is based on the GNExB2 Series enclosure, the junction box is closed with a single piece molded threaded cover.

See Annex for additional information.

CONDITIONS OF CERTIFICATION: YES as shown below:

The enclosure is non-conducting and may generate an ignition-capable level of electrostatic charges under certain extreme conditions. The user should ensure that the equipment is not installed in a location where it may be subjected to external conditions (such as high-pressure steam) which might cause a build-up of electrostatic charges on non-conducting surfaces. Additionally, cleaning of the equipment should be done only with a damp cloth.

Accessible metal parts are capable of retaining a stored capacitance of 10pF therefore the end user shall take the appropriate action to reduce the risks of ignition associated with discharging this capacitance.

Repair of the flamepath's is not permitted.

GNExB2X21 models shall not be mounted with the lamp down.



IECEX Certificate of Conformity

Certificate No: IECEx UL 15.0003X

Issue No: 1

Date of Issue: 2016-06-30

Page 5 of 5

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above):

Issue 1: This variation to report introduces the Large LED Beacon model numbers GNExB2LD2DC024, GNExB2LD2AC115, GNExB2LD2AC230 to the certified range.

Correction of typo, temperature rating T135°C in "Code" to be T130°C and thus match information shown in Ratings table contained under General Product Information.

Annex:

[Annex to IECEx UL 15.0003X Issue 1.pdf](#)